

Clarius®



Clarius® Brackets

| | |
|--|--|
| <p>SMB1</p>  | <ul style="list-style-type: none"> • 'L' wall mount bracket for single illuminator • Compatible with all Clarius Infra-Red & White light illuminators • Allows up to 180 degrees rotation • Fully adjustable (left, right, up & down) • Stainless steel construction (black powder coated) |
| <p>DMB1</p>  | <ul style="list-style-type: none"> • Dual illuminator mounting bracket compatible with all Clarius Infra-Red & White-Light illuminators • Doubles the angle of illumination • Increases illumination distance by a factor of 1.4x when using two equivalent illuminators • Mix-and-match illuminators (angle & distance) • Mix-and-match Infra-Red & White-Light illuminators for Hybrid models • Fully adjustable (left, right, up & down) • Includes IP67 rated junction box • Stainless steel construction (black powder coated) |
| <p>TMB1</p>  | <ul style="list-style-type: none"> • Triple Illuminator mounting bracket compatible with all Clarius Infra-Red & White- Light illuminators • Triples the angle of illumination • Increases illumination distance by a factor of 1.7x when using three equivalent illuminators • Mix-and-match illuminators (angle & distance) • Mix-and-match Infra-Red & White-Light illuminators for Hybrid models • Fully adjustable (left, right, up & down) • Includes IP67 rated junction box • Stainless steel construction (black powder coated) |
| <p>PMB1</p>  | <ul style="list-style-type: none"> • Single Pole mounting bracket compatible with all Clarius Infra-Red & White-Light illuminators including SMB1, DMB1 and TMB1 • Supplied with stainless steel straps to fit 7.5 to 20 cm diameter pole • Stainless steel construction |
| <p>PMB2</p>  | <ul style="list-style-type: none"> • Double Pole mounting bracket compatible with all Clarius Infra-Red & White-Light illuminators including SMB1, DMB1 and TMB1 • Supplied with stainless steel straps to fit 7.5 to 20 cm diameter pole • Stainless steel construction |

